

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 310 876 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
14.05.2003 Bulletin 2003/20

(51) Int Cl.⁷: G06F 11/14, G06F 3/06

(21) Application number: 01126947.9

(22) Date of filing: 13.11.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Kitamura, Manabu, c/o Hitachi, Ltd.
Chiyoda-ku, Tokyo 100-8220 (JP)
• Arai, Kouji, c/o Hitachi, Ltd.
Chiyoda-ku, Tokyo 100-8220 (JP)


(71) Applicant: Hitachi, Ltd.
Chiyoda-ku, Tokyo 101-8010 (JP)

(74) Representative: Strehl Schübel-Hopf & Partner
Maximilianstrasse 54
80538 München (DE)

(54) Computer system

(57) In the computer system where the plurality of host computers (1, 1') and the plurality of storage apparatuses (2, 2') are interconnected, in order to carry out the data migration between the storage apparatuses (2, 2') transparently to the host computers (1, 1'), the back end server (3) provides the virtual disk to the host computers (1, 1'). From the host computers (1, 1'), at first, the virtual disk looks the same as the old storage subsystem (2). When migrating the data from the old storage subsystem (2) to the new storage subsystem (2'), at first, the back end server (3) instructs the data migration unit (24) to execute the data migration processing. Subsequently, the back end server (3) switches the setting of the virtual disk, thereby causing the virtual disk to correspond to the new storage subsystem (2').

FIG. 1



Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to a data access method to a storage apparatus system in an information processing system or the like. More particularly, it relates to a data migration method within the storage apparatus system.

[0002] An increasingly prevailing trend is that a plurality of platforms and a plurality of storage apparatuses are connected to each other so that the platforms and the storage apparatuses will be integrated into so-called a single network. Here, the platforms are, for example, a personal computer, a workstation, and a mainframe which employ mutually different architectures and operating systems. This resultant network is generally referred to as "SAN (Storage Area Network)", which is a technical term corresponding to "LAN (Local Area Network)" formed by connecting a plurality of computers by a network such as Ethernet. In SAN, usually, the computers and the storage apparatuses are connected using a communication line referred to as "Fibre Channel" formed of an optical cable or a copper wire.

[0003] It has been pointed out that SAN has several advantages. The first advantage is to provide an environment where the storage apparatuses can be accessed from the plurality of computers in common. The second advantage is that the data transfers among the storage apparatuses are made possible by interconnecting the storage apparatuses among themselves. This makes it possible to implement backups or data copies among the storage apparatuses without imposing a load onto the host computers, thereby, at the time of the storage apparatuses' failure, allowing the switching to storage apparatuses included in a secondary system. Thirdly, until now, the individual storage apparatuses have been connected to the individual computers, respectively. As a result, managing the individual storage apparatuses (i.e., monitoring the states of the apparatuses, and modifying the settings thereof) has been possible only from the individual computers connected thereto. In SAN, however, it becomes possible to manage all the storage apparatuses from an arbitrarily specified computer. Also, the conventional SCSI (Small Computer System Interface) could connect only 16 appliances at the maximum. Meanwhile, Fibre Channel can connect 100 or more appliances on-line, thereby making it possible to obtain an easy scalability.

[0004] In recent years, a large number of products for implementing SAN have appeared. There exists, however, none of the products that actually make full utilization of the above-described advantages. In the scalability in particular, although the on-line connection of the appliances has been made physically possible, fundamental technologies for taking full advantage of the scalability are lacking. In SAN, for example, when additionally installing a new disk apparatus for the replacement

of an existing disk apparatus, the additional installation of the appliance can be carried out on-line. Concerning the data migration, however, the users usually need to explicitly instruct the data migration into the new disk apparatus after switching the connection off-line once. For the users to enjoy the merits by the appliance additional-installation during the on-line, in addition to the mere hardware additional-installation, it is also required to carry out the data migration or the like transparently to the users, i.e., in such a manner that the users are unconscious of the data migration or the like, in accompaniment with the hardware additional-installation.

[0005] Concerning the on-line data migration among the disk apparatuses, U.S. Patent No. 5,680,640 has disclosed its example. The example in U.S. Patent No. 5,680,640, which describes the data migration where the disk apparatuses designed for a mainframe are assumed, utilizes communication lines for connecting the disk apparatuses, and only disconnects the connections among the hosts and the disk apparatuses for a short time. After that, the example allows the data migration among the disk apparatuses to be implemented transparently to the users.

[0006] U.S. Patent No. 5,680,640 allows the data migration among the disk apparatuses to be implemented unlimitedly transparently to the users. However, this is the data migration method where the for-mainframe-designed disk apparatuses are assumed, and thus this method is inapplicable to SAN. In the for-mainframe-designed disk apparatuses as disclosed in U.S. Patent No. 5,680,640, when replacing an old disk apparatus by a new disk apparatus, the setting on the disk apparatus side makes it possible to make the new disk apparatus look as if it were the old disk apparatus when seen from the host side. This is made possible by manipulating the setting of device numbers or the like of the disk apparatuses.

[0007] However, in SAN, especially in the case of, e.g., the Fibre Channel environment, the individual unique IDs assigned to the individual disk apparatuses are determined by the negotiation among the appliances (i.e., the disk apparatuses, and a fibre channel switch) included in the network. Accordingly, the setting made by the users never changes the IDs. This condition, when using the data migration method in U.S. Patent No. 5,680,640, makes it impossible to make the new disk apparatus disguise the old disk apparatus with respect to the host computers. Consequently, in reality, it is impossible to implement the data migration that is transparent to the hosts and the users.

SUMMARY OF THE INVENTION

[0008] It is an object of the present invention to provide a system that is transparent to the hosts and the users, and that is capable of making full utilization of the scalability of SAN.

[0009] The computer system in the present invention

includes, for example, host computers, a back end computer (back end server), a plurality of storage subsystems, and a switch for connecting at least the host computers with the back end computer. The host computers access each storage subsystem via the back end computer. Here, the back end computer provides one virtual disk apparatus or a plurality of virtual disk apparatuses to the host computers. If the host computers issue access requests to the virtual disk apparatus/apparatuses, the back end computer issues an appropriate request to the storage subsystems connected thereto actually, depending on the type of the virtual disk apparatus/apparatuses to which the requests have been issued.

[0010] According to the present invention, it becomes possible to implement all the data manipulations, such as the data migration among the disk apparatuses and on-line extension of the disk capacities, completely transparently to the host computers.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011]

FIG. 1 is a block diagram for illustrating the configuration example of a computer system in an embodiment of the present invention;

FIG. 2 is a table configuration diagram for illustrating a table used by a data migration unit toward a new storage subsystem of the present invention;

FIG. 3 is a flow chart for illustrating the flow of a data migration processing performed by the data migration unit of the present invention;

FIG. 4 is a flow chart for illustrating the flow of a processing performed by the data migration unit when a writing request arrives during the data migration processing;

FIG. 5 is a flow chart for illustrating the flow of a processing performed by the data migration unit when a reading request arrives during the data migration processing;

FIG. 6 is a flow chart for illustrating the flow of a processing performed by a back end server when the data migration processing from an old storage subsystem to the new storage subsystem is performed in the computer system in the embodiment of the present invention;

FIG. 7 is a block diagram for illustrating the configuration example of another computer system embodying another embodiment of the present invention;

FIG. 8 is a block diagram for illustrating the configuration example of another computer system embodying another embodiment of the present invention; and

FIG. 9 is a block diagram for illustrating the configuration example of another computer system embodying another embodiment of the present invention.

DESCRIPTION OF THE EMBODIMENTS

[0012] FIG. 1 is a block diagram for illustrating the configuration example in an embodiment of a computer system to which the present invention is applied. The computer system includes hosts 1, 1', an old storage subsystem 2, a new storage subsystem 2', a back end server 3, and a fibre channel switch 4.

[0013] The host 1 includes an operating system 11, an application program 12, and an interface 13. Although, actually, the operating system 11 and the application program 12 operate on a CPU 14 and a memory 15 on the host 1, the detailed explanation will be omitted concerning these hardware configuration components. Actually, the general environment is a one where, like the host 1, a plurality of host computers other than the host 1 are connected, but only the operation of the host 1 as the host computers will be described for simplifying the operation of the present invention. In the host 1', the components with apostrophe are the same as or equivalent to the corresponding components in the host 1.

[0014] The old storage subsystem 2 includes a disk 21, a controller 22, and an interface 23. Even if the disk 21 is a logical drive that is made to disguise a single logical disk apparatus by integrating a plurality of physical disks, the contents of the present invention remain unchanged. The interface 23 is connected to the fibre channel switch 4.

[0015] As is the case with the old storage subsystem 2, the new storage subsystem 2' also includes a disk 21', a controller 22', and an interface 23'. The point that differs from the old storage subsystem 2 is that a data migration unit 24 is included in the controller 22'.

[0016] The back end server 3 includes a virtual device driver 31 and interfaces 32 and 33. The virtual device driver 31 is a software that operates on a CPU 35 and a memory 36 on the back end server 3, and it is possible for the user to modify the setting thereof from the outside or to replace the program itself. The detailed explanation will be omitted regarding the hardware configuration components such as the CPU 35 and the memory 36.

[0017] The fibre channel switch 4, which includes a plurality of ports 41a, 41a', 41b, 41c, 41d, and 41e (hereinafter, abbreviated generically as a port 41), is used for interconnecting the host 1, the old storage subsystem 2, the new storage subsystem 2', and the back end server 3. Accessing any of the ports 41a', 41b, 41c, 41d, and 41e is possible from the port 41a. This condition allows the host 1 to directly access the old storage subsystem 2 and the new storage subsystem 2' from the ports 41b and 41e, respectively. In the present embodiment, however, it is assumed that, basically, the host 1 accesses the old storage subsystem 2 and the new storage subsystem 2' all through the back end server 3.

[0018] The explanation will be given below concerning the role of the back end server 3. The virtual device driver 31 makes the back end server 3 look as if it were one disk apparatus or a plurality of disk apparatuses

when seen from the host 1. In the present embodiment, it is assumed that, when the host 1 looks at the back end server 3 through the port 41d, the host 1 sees one disk apparatus as if it were connected to the port 41d. Hereinafter, this disk apparatus will be referred to as a virtual disk.

[0019] The virtual device driver 31 is set so that, when seen from the host 1, the virtual disk at first looks the same as the disk apparatus 21 in the old storage subsystem 2. Namely, if the host 1 accesses, for example, a logical block address (LBA) 0 in the virtual disk, the virtual device driver 31 accesses LBA 0 in the disk apparatus 21 via the interface 32 and the port 41c, then returning the result back to the host 1 via the interface 33 and the port 41d. In the embodiment of the present invention, although the interface 32 is used for accessing the disk 21 or the disk 21' and also the interface 33 is used for the communications with the host 1, it is possible to cause a single interface to play these two roles.

[0020] Here, attention should be paid to the following point: Modifying the setting of the virtual device driver 31 makes it possible to make the virtual disk look as if it were the disk apparatus 21' in the new storage subsystem 2'. When this setting modification is performed, the virtual disk that the host computer sees remains unchanged. Even if the virtual disk is modified from the disk 21 to the disk 21' by the setting modification of the virtual device driver 31, the port ID and LUN of the virtual disk that the host 1 is made to see remain unchanged. As a result, the host 1 has none of the recognition that the actually accessed disk has been changed.

[0021] Next, the explanation will be given below regarding the data migration unit 24 in the new storage subsystem 2'. The data migration unit 24 has a unit similar to the unit disclosed in U.S. Patent No. 5,680,640. If the data migration is instructed, the data migration unit 24 reads the data sequentially from the front-head of the disk 21 in the old storage subsystem 2, then writing the data into the disk 21' in the new storage subsystem 2'. Moreover, the unit 24 has a table (i.e., 100 in FIG. 2) for recording whether or not the data migration has been finished in an each-block unit or in a plural-block unit. If a reading access arrives from the host computer during the data migration processing, the unit 24 makes reference to this table. Then, the unit 24 reads the data from the disk 21 in the old storage subsystem 2 with respect to regions where the data migration is not over, and returns the data in the disk 21' in the new storage subsystem 2' with respect to regions where the data migration is over.

[0022] FIG. 2 illustrates the table that the data migration unit 24 has. The data migration unit 24 copies the data on each block basis from the disk 21 in the old storage subsystem 2 into the disk 21' in the new storage subsystem 2'. The table 100 includes a flag 102 for each logical block address 101. In the present embodiment, the case where the flag 102 is "1" indicates that the data at the address has been copied already from the disk

21 into the disk 21', and the case where the flag 102 is "0" indicates that the data at the address has not been copied yet. In the data migration processing, or in the data reading/writing processing based on the requests from the host computer during the data migration processing, the unit 24 makes reference to this table.

[0023] Referring to FIG. 3, the explanation will be given below concerning the flow of the migration processing performed by the data migration unit 24. First, a counter B is prepared, and the initial value is set to be "0" (step 2001). Next, reference is made to the table 100, thereby checking whether or not the flag 102 for LBA B is "1" (step 2002). If the flag is "1", it means that the data migration is over, and accordingly the counter B is incremented by "1" (step 2005). Also, at the step 2002, if the flag 102 is "0", the data is copied from the disk 21 into the disk 21' (step 2003). Then, the corresponding flag 102 in the table 100 is updated to "1" (step 2004), and the processing goes to the step 2005. At a step 2006, it is checked whether or not the processing has been executed to the final LBA of the disk 21. Namely, it is checked whether or not B has exceeded the final LBA of the disk 21. If B has exceeded the LBA, the processing is completed. If not, the processing goes back to the step 2002, then being repeated.

[0024] Next, referring to FIG. 4, the explanation will be given below regarding a processing in the case where, while the data migration unit 24 is executing the data migration processing in FIG. 3, there has arrived the writing request from the host computer, i.e., the back end server 3 (or the host 1) in the present embodiment. In the case where the block unit of the written-in data from the host coincides with the unit of LBA, this processing is simple: At a step 2101, the data is written into the disk 21' in the new storage subsystem 2', and at a step 2102, the flag 102 for the corresponding LBA in the table 100 is updated to "1". Namely, with respect to the LBA for which the writing processing has been performed during the data migration processing, it becomes unnecessary to execute the data migration from the disk 21 in the old storage subsystem 2.

[0025] Referring to FIG. 5, the explanation will be given below concerning a processing in the case where, while the data migration unit 24 is executing the data migration processing in FIG. 3, there has arrived the reading request from the host computer, i.e., the back end server 3 in the present embodiment. At a step 2201, reference is made to the flag 102 for the LBA within the table 100 for which there has arrived the reading request. At a step 2202, it is checked whether or not the flag 102 for the corresponding LBA is "1", thereby branching the processing. If the flag is "1", the data migration from the disk 21 in the old storage subsystem 2 into the disk 21' in the new storage subsystem 2' has been finished with respect to the LBA, and accordingly the data is read from the disk 21' (step 2203). If the flag 102 is "0", the data migration has been not finished yet with respect to the LBA, and accordingly the data is cop-

ied from the disk 21 into the disk 21' once (step 2205). Subsequently, the flag 102 in the table 100 is updated to "1" (step 2206). After that, the processing goes to the step 2203 or after. At a step 2204, the read-out data is passed over to the back end server 3, thereby completing the processing.

[0026] In this way, it turns out that, even during the data migration, the back end server 3 always executes the data reading/writing with respect to the disk 21' in the new storage subsystem 2'.

[0027] Next, concerning the data migration processing from the old storage subsystem 2 to the new storage subsystem 2' in the system of the present embodiment, the flow of the entire system will be explained. When executing the data migration, the user instructs the back end server 3 to start the migration. The data-migration-processing starting instruction from the back end server 3 to the new storage subsystem 2' is transmitted to the new storage subsystem 2' via the interface 32.

[0028] FIG. 6 explains the flow of a virtual disk's setting modification processing executed by the back end server 3. If the back end server 3 receives the migration instruction, at first, the server 3 stops the operation of the virtual disk by the virtual device driver 31 (step 1001). This interrupts the access from the virtual device driver 31 to the old storage subsystem 2. As a result, even if the virtual device driver 31 receives an access command to the virtual disk from the host 1, the driver 31 returns no response until the access halt is cleared. Next, a storage apparatus management program 34 instructs the new storage subsystem 2' to start the data migration processing illustrated in FIG. 3 (step 1002). Moreover, at a step 1003, the setting of the virtual disk that the virtual device driver 31 has caused the host 1 to access the disk 21 so far is modified so that an access to the disk 21' will be made. Finally, at a step 1004, the access halted at the step 1001 is restarted. When the access to the virtual disk from the host 1 is restarted, if accesses have been made to the virtual disk from the host 1 between the step 1001 and the step 1002, the accesses are all carried out with respect to the disk 21'.

[0029] Also, in the present embodiment, there has been provided the connection configuration where the old and the new storage subsystems 2 and 2' and the back end server 3 are directly connected to the switch. However, in the case where, unlike the example in FIG. 1, the additionally-installed new storage subsystem 2' does not include the data migration unit 24, the data migration unit 24 is included on the side of the back end server 3 as is illustrated in FIG. 7. Then, the back end server is caused to execute the data migration processing, which makes it possible to implement the same processing.

[0030] Moreover, in the present embodiment, there has been provided the back end server 3, thereby presenting the processing for making the host see the virtual disk. As illustrated in FIG. 8, however, it is also possible to implement a configuration where the virtual de-

vice driver 31, the storage apparatus management program 34, and the data migration unit 24 are included in the fibre channel switch 4. Also, as illustrated in FIG. 9, it is also possible to implement even a configuration where the storage subsystems 2 and 2' are connected to each other via an interface 37 of the back end server 3. In that case, the data migration unit 24 may also be included on the side of the back end server 3.

[0031] Although, in the present embodiment, there has been presented the example where the data migration among the disks can be executed transparently to the host computer, there exist a variety of examples to which the embodiment is applicable. If the virtual device driver causes the virtual disk to correspond to the real storage apparatuses, it does not matter at all to the host computer which storage apparatus actually stores the data. This makes the embodiment applicable to the following systems, for example: A storage apparatus management system where a virtual disk with a necessary minimum capacity is defined usually, and a virtual disk with a necessary capacity can be prepared dynamically at a point-in-time when it becomes required, and a system that, depending on the data access frequency, migrates the data transparently to the host and dynamically from a low-rate disk to a high-rate disk.

Claims

1. A computer system, comprising:

host computers (1, 1'),
a plurality of storage apparatus (2, 2'), a unique ID that is unchangeable from outside being assigned to each of said storage apparatus (2, 2'),
a switch (4) for interconnecting said host computers (1, 1') with said plurality of storage apparatus (2, 2'), and
a back end server (3) connected to said host computers (1, 1') through said switch (4) for managing said plurality of storage apparatus (2, 2') so as to provide a virtual storage apparatus to said host computers (1, 1'), wherein said back end server (3) dynamically modifies a storage apparatus from an arbitrary storage apparatus (2) of said plurality of storage apparatus (2, 2') to another storage apparatus (2') thereof (FIG. 6), said storage apparatus being caused to disguise said virtual storage apparatus.

2. The computer system of claim 1, wherein, while dynamically modifying said storage apparatus caused to disguise said virtual storage apparatus, said back end server (3) makes no response to an access request made from said host computers (1, 1') to said virtual storage apparatus.

3. The computer system of claim 1, further comprising:

a data migration unit (24) for migrating data in said arbitrary storage apparatus (2) into said another storage apparatus (2') on a fixed-sized data block (LBA) (101) basis, and
 a table (100) holding a flag (102) for indicating a data migration state on said fixed-sized data block (101) basis, wherein, in response to a writing request for said fixed-sized data block (101) from said back end server (3), said data migration unit (24) writes said data block (101) into a corresponding storage position in said another storage apparatus (2') and after that, modifies the migration state of a flag (102) to "data migration completed" (FIG. 4), said flag (102) corresponding to said written-in data block (101) in said table (100).

4. The computer system of claim 1, further comprising:

a data migration unit (24) for migrating data in said arbitrary storage apparatus (2) into said another storage apparatus (2') on a fixed-sized data block (LBA) (101) basis, and
 a table (100) holding a flag (102) for indicating a data migration state on said fixed-sized data block (101) basis, wherein, in response to a reading request for said fixed-sized data block (101) from said back end server (3), wherein said data migration unit (24):

obtains the migration state of a flag (102) by making reference to said table (100), said flag (102) corresponding to said data block (101) for which said reading request has been made, and, if said migration state is "data migration uncompleted", migrates said corresponding data block (101) from said arbitrary storage apparatus (2) into said another storage apparatus (2'),
 modifies the migration state of said flag (102) to "data migration completed", said flag (102) corresponding in said table (100) to said data block (101) for which said reading request has been made, and after that,
 passes, to said back end server (3), said data block (101) for which said reading request has been made. (FIG. 5)

5. The computer system of claim 1, wherein said another storage apparatus (2') or said back end server (3) has a data migration unit (24).

6. The computer system of claim 1, wherein said back end server (3) and a data migration unit (24) are

built in said switch (4).

7. A storage apparatus switching method in a computer system which comprises host computers (1, 1'), a plurality of storage apparatus (2, 2'), a unique ID that is unchangeable from outside being assigned to each of said storage apparatus (2, 2'), and a switch (4) for interconnecting said host computers (1, 1') with said plurality of storage apparatus (2, 2'), said storage apparatus switching method comprising the steps of:

causing at least one of said plurality of storage apparatus (2, 2') to disguise a virtual storage apparatus so as to provide said virtual storage apparatus to said host computers (1, 1'), and modifying at least one of said storage apparatus (2, 2') dynamically from an arbitrary storage apparatus (2) to another arbitrary storage apparatus (2'), at least one of said storage apparatus (2, 2') being caused to disguise said virtual storage apparatus. (FIG. 6)

8. The method of claim 7, wherein, while at least one of said storage apparatus (2, 2') caused to disguise said virtual storage apparatus is being dynamically modified, no response is made to an access request made from said host computers (1, 1') to said virtual storage apparatus.

9. A storage apparatus' data migrating method in a computer system which comprises host computers (1, 1'), a plurality of storage apparatus (2, 2'), a unique ID that is unchangeable from outside being assigned to each of said storage apparatus (2, 2'), and a switch (4) for interconnecting said host computers (1, 1') with said plurality of storage apparatus (2, 2'), said storage apparatus' data migrating method comprising the steps of:

causing at least one of said plurality of storage apparatus (2, 2') to disguise a virtual storage apparatus so as to provide said virtual storage apparatus to said host computers (1, 1'), creating a table (100) holding a flag (102) for indicating a data migration state on a fixed-sized data block (LBA) (101) basis, prohibiting a response to an access request made from said host computers (1, 1') to said virtual storage apparatus, modifying dynamically an arbitrary storage apparatus (2) to another arbitrary storage apparatus (2') as at least one of said storage apparatus (2, 2') caused to disguise said virtual storage apparatus (FIG. 6), restarting said response to said access request made from said host computers (1, 1') to said virtual storage apparatus,

migrating said data block (101) into said another arbitrary storage apparatus (2') on said fixed-sized data block (101) basis, said data block (101) being stored into said arbitrary storage apparatus (2), and

executing, toward said another arbitrary storage apparatus (2'), an access to said data block (101) to be performed in response to said access request made from said host computers (1, 1').

10. The method of claim 9, further comprising the steps of:

writing said fixed-sized data block (101) into a corresponding storage position in said another arbitrary storage apparatus (2') in response to a writing request for said fixed-sized data block (101) from said host computers (1, 1'), and after that,

modifying a migration state of a flag (102) to "data migration completed" (FIG. 4), said flag (102) corresponding to said written-in data block (101) in said table (100).

11. The method of claim 9, further comprising the steps of:

obtaining, in response to a reading request for said fixed-sized data block (101) from said host computers (1, 1'), the migration state of a flag (102) by making reference to said table (100), said flag (102) corresponding to said fixed-sized data block (101) for which said reading request has been made, and, if said migration state is "data migration uncompleted", migrating, from said arbitrary storage apparatus (2) into said another arbitrary storage apparatus (2'), said data block (101) for which said reading request has been made, modifying the migration state of said flag (102) to "data migration completed", said flag (102) corresponding in said table (100) to said data block (101) for which said reading request has been made, and after that, sending said read-out data block (101) to said host computers (1, 1'). (FIG. 5)

12. A computer system, comprising:

a plurality of computers (1, 1'),
a plurality of storage apparatus (2, 2'), and
a switch (4) for interconnecting said plurality of computers (1, 1') with said plurality of storage apparatus (2, 2'), said computer system having means for providing a virtual storage apparatus to said plurality of computers (1, 1'), said virtual storage apparatus being a storage apparatus

that is in a correspondence with at least one of said plurality of storage apparatus (2, 2'), said means for providing said virtual storage apparatus modifying said correspondence dynamically.

13. The computer system of claim 12, wherein, when said means for providing said virtual storage apparatus has modified said correspondence dynamically, said means prevents said plurality of computers (1, 1') from seeing that said correspondence has been changed.

14. The invention of any preceding claim, wherein said switch (4) is a fibre channel.

FIG. 1




FIG. 2

100	101	102
ADDRESS	FLAG	
LBA0	1	
LBA1	1	
LBA2	0	
LBA3	0	
LBA4	1	
⋮	⋮	
LBAn	0	

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 6947

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	WO 01 80013 A (NAHUM NELSON ;STOREAGE NETWORKING TECHNOLOGI (IL)) 25 October 2001 (2001-10-25) * page 9, line 15 - page 16, line 8 * * page 20, line 32 - line 45; figures 1-8,13,15,18 *	1-14	G06F11/14 G06F3/06
Y	EP 1 130 514 A (HITACHI LTD) 5 September 2001 (2001-09-05) * column 5, line 11 - column 14, line 29 * * column 15, line 51 - column 19, line 17; figures 1,6,8-11,13-18 *	1-14	
D,A	US 5 680 640 A (YANAI MOSHE ET AL) 21 October 1997 (1997-10-21) * column 3, line 66 - column 7, line 39; figures *	1-14	
E	PATENT ABSTRACTS OF JAPAN vol. 2002, no. 03, 3 April 2002 (2002-04-03) & JP 2001 331355 A (HITACHI LTD), 30 November 2001 (2001-11-30) * abstract *	1-14	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G06F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 October 2002	Examiner Moens, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 6947

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0180013	A	25-10-2001	AU 4679901 A WO 0180013 A1	30-10-2001 25-10-2001
EP 1130514	A	05-09-2001	JP 2001249853 A EP 1130514 A2	14-09-2001 05-09-2001
US 5680640	A	21-10-1997	DE 69622253 D1 EP 1160654 A1 EP 0789877 A1 JP 10508967 T WO 9709676 A1 US 6240486 B1 US 2001001870 A1 US 6108748 A US 5896548 A US 2002004890 A1	14-08-2002 05-12-2001 20-08-1997 02-09-1998 13-03-1997 29-05-2001 24-05-2001 22-08-2000 20-04-1999 10-01-2002
JP 2001331355	A	30-11-2001	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82